

[illegible]

60.50											
60.00											
59.50											
59.00											
58.50											
58.00											
Mhor 1:500 Mvert 1:50											
KAEVU TÄHIS	SK-35	SK-34	SKPY-33	SK-32	SK-31	SK-30	SK-29	SK-28	SK-27	SK-26	
OLEMASOLEVA MAAPINNA KÕRGUS (m ABS)	64.45	64.50	64.20	63.85	63.60	63.40	63.00	62.85	62.60	62.00	
PROJEKTEERITUD MAAPINNA KÕRGUS (m ABS)	64.45	64.50	64.25	63.83	63.62	63.44	63.02	62.88	62.58	61.98	
TORU RENNII KÕRGUS (m ABS)	62.87	61.80 62.66	61.65	61.39	61.16	60.98	60.54	60.40	60.05	59.43	
TORU RAJAMISSÜGAVUS	1.58	1.84 2.70	2.60	2.44	2.46	2.46	2.48	2.48	2.53	2.55	
LANG	21.2	0.010	215.0	PE/PP SN8 Die315							
TORU LÄBIMÕÖT	PE/PP SN8 Die250										
VAHEKAUGUSED (m)	21.2	13.3	24.5	20.8	15.9	39.9	12.7	32.4	55.7		
SIRGESTATUD TRASSI PLAAN											

Märkused

1. Torustiku asukoht vt joonis VK-3.
2. Tingmärgid vt joonis VK-A.
3. Ehituskaeviku ja teekatete taastamise tüüpistloiked vt joonis VK-B.