

Plurio LED

THORN

96265469 PLU O LED 18L70 R/S BP CL1 D60 L730

LED 41W LED_PLU2_RS_3326	IP66	IK08				
--------------------------	------	------	--	--	--	--

Plurio LED


Decorative, post-top lantern with LED package with electronic driver. Class I electrical, IP66, IK08. Base in cast Aluminium, powder coated silver-grey. Canopy in original shape, made from Aluminium textured silver-grey (close to RAL9006). UV stabilised Polycarbonate (PC) clear diffuser with anti-glare prisms. Internal symmetric reflector. Equipped with power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Supplied complete in one box. Complete with 3000K LED

To be post top mounted on a spigot of Ø60mm, length 75mm.


Dimensions: Ø564 x 567 mm
Total power: 41 W
Weight: 7.2 kg
Scx: 0.074m²
Luminaire efficacy: 81 lm/W



TLG_PLRO_F_LEDSYM.jpg



TLG_PLRO_M_LMPShd60.wmf



TLLA_PLU18L70RS3KG32_DC.ltd

Lamp position: STD - standard
Light Source: LED
Luminaire luminous flux*: 3326 lm
Luminaire efficacy*: 81 lm/W
Lamp efficacy: 81 lm/W
Colour Rendering Index min.: 70

Correlated colour temperature*: 3000 Kelvin
Rated useful life (B10)*:
100000h L90 at 25°C
Ballast: 1x EL2
Luminaire input power*: 41 W
Dimming: DIM_LED
LOR: 1,00 ULOR: 0,00 DLOR: 1,00

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Colour temperature is subject to a tolerance of up to ± 150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.

© Thorn Lighting